

APPARATUS AND METHOD FOR MOUNTING A TIRE CONDITION SENSOR CAPSULE TO A WHEEL RIM

BACKGROUND OF THE INVENTION

5 1. Field of Invention

This invention relates to tire condition sensing and more particularly to an apparatus and method for mounting a tire condition sensor capsule to a wheel rim.

10 2. Description of Related Art

15 The use of tire condition sensors is becoming increasingly popular. Some countries are implementing requirements that certain vehicles employ such devices to improve safety. Various schemes have been developed for mounting tire condition sensors to vehicle wheels. Some mount sensors to the outside of the wheel while others mount them to the inside of the wheel (inside the tire). Mounting inside the tire is a preferable method.

20 Various tire condition sensors operable to be mounted inside the tire are available. These sensors may include pressure sensors, temperature sensors or the like and some include transmitter circuitry for transmitting a measured tire condition value to a remote transmitter. Each manufacturer of a tire condition sensor will package its device or devices in a package of its own design. In general, tire condition sensor units are available in a wide variety of shapes and sizes to accommodate the circuitry they employ. 25 However, some packaging can be susceptible to damage, especially during tire installation. In general, sensor packages that have protruding objects or sharp corners can be susceptible to catching on a tire as the tire is installed.

30 In addition each wheel rim on which a tire condition sensor might be installed has its own special requirements in relation to permissible weight of the sensor, profile, and ease of installation. Typically, this has been dealt with by providing separately packaged condition sensors for each type of wheel rim.

With the risk of damage to the sensor during tire installation, or removal, if a sensor is damaged during either of these procedures, an entirely new sensor must be installed. Damage to the sensor usually involves damage to the mounting components such as tabs or other structure on the sensor unit itself, requiring replacement of the entire sensor, even if only the sensor case, for example is broken.

What would be desirable is a way of mounting tire condition sensors in a manner that protects the sensor unit while at the same time permitting easy and inexpensive installation and removal, without requiring a brand new sensor unit when only mounting components are damaged. The present invention addresses this need.

SUMMARY OF THE INVENTION

The present invention addresses the above needs by providing an apparatus and method for mounting a tire condition sensor capsule to a wheel rim.

In accordance with one aspect of the invention there is provided an apparatus for mounting a tire condition sensor capsule to a wheel rim. The apparatus may include a housing having a receptacle having a shape complementary to the capsule to receive the capsule snugly therein. Additionally the apparatus may include a lock on the housing, cooperating with a surface on the capsule to lock the housing to the capsule, and a connector for connecting the housing to the wheel rim such that the capsule is between a portion of the wheel rim and the receptacle.

The housing may include a wall and may be rigid and/or may be formed of injection molded plastic.

The lock may be on the wall of the housing. The wall may have first and second spaced apart side portions between which the capsule is received and the lock may be on one of the first and second side portions. The lock may

include first and second clips on the first and second side portions, respectively.

5 The first and second side portions may have first and second edge extremities, respectively, and the lock may include first and second clips on the first and second edge extremities, respectively, which cooperate with the capsule to lock the housing to the capsule. The lock may further include third and fourth clips spaced apart from the first and second clips respectively, on the first and second edge extremities. The first and second edge extremities may have first and second contact surfaces respectively for contacting the wheel rim and the contact surfaces may have a concave shape complementary to the shape of the wheel rim.

10
15 The wall may have a weight reducing void therein and may have first and second spaced apart side portions between which the capsule is received and the wall may have an intermediate portion extending between the first and second side portions. The intermediate portion may have a weight reducing void therein and may have first and second spaced apart weight reducing voids therein.

20 The wall may include first and second opposite end portions extending from the intermediate portion, the capsule being received between the first and second side portions and the first and second opposite end portions. The first and second wall portions may be wider than the first and second opposite end portions such that the first and second end side portions completely cover respective side portions of the capsule and such that the first and second opposite end portions only partially cover respective end portions of the capsule.

25
30 The connector may include first and second fastener receivers on the first and second opposite end portions of the housing. The first and second fastener receivers may be molded into the housing, for example. Alternatively, the

connector may include a valve stem connector operable to cooperate with a valve stem of the wheel to secure the housing to the wheel rim. The valve stem connector may include a valve stem receptacle in the housing for receiving a portion of the valve stem, and may further include an opening in the housing, in communication with the valve stem receptacle, for receiving a fastener operable to fasten the valve stem in the valve stem receptacle.

Alternatively, the connector may include a strap holder operable to cooperate with a strap that extends around the wheel to secure the housing to the wheel. The strap holder may be formed in the housing and may include first and second slots formed in the housing, the slots being operable to receive the strap. The wall may have first and second opposite end portions and the strap holder may include first and second openings in the first and second end portions respectively, for receiving the strap.

In accordance with another aspect of the invention there is provided a method for mounting a tire condition sensor capsule to a wheel rim. The method may include receiving the capsule in a housing having a receptacle having a shape complementary to the capsule, locking the capsule in the housing, and connecting the housing to the wheel rim such that the capsule is between a portion of the wheel rim and the receptacle.

Receiving may include receiving the capsule between first and second side portions and between first and second end portions of a wall of the housing.

Locking may include engaging a clip on the housing with a surface on the capsule.

Connecting the housing to the wheel rim may include fastening first and second end portions of the housing to corresponding mounting surfaces on the wheel rim. Connecting the housing to the wheel rim may alternatively include receiving a portion of a valve stem of the wheel rim in a receptacle in

the housing and fastening the portion of a valve stem of the wheel rim in the receptacle in the housing.

Alternatively, connecting the housing to the wheel rim may involve engaging a strap extending around the wheel rim with openings in the housing.

In accordance with yet another aspect of the invention there is provided an apparatus for mounting a tire condition sensor capsule to a wheel rim. The apparatus may include a device for holding and protecting the capsule, a device for locking the capsule in the device for holding and protecting, and a device for connecting the device for holding and protecting to the wheel rim such that the capsule is between the device for holding and protecting and the wheel rim.

The device for holding and protecting may include a receptacle for receiving the capsule.

The device for locking may include a clip on the device for holding and protecting, the clip being operable to engage a surface of the capsule.

The device for connecting may include first and second fastener receivers on the device for holding and protecting.

Alternatively, the connecting device may include a valve stem connector operable to cooperate with a valve stem of the wheel to secure the device for holding and protecting to the wheel rim.

Alternatively, the connecting device may include a strap holder operable to cooperate with a strap that extends around the wheel to secure the device for holding and protecting to the wheel rim.

The device for holding and protecting may include a housing having a receptacle for receiving the capsule.

5 In accordance with another aspect of the invention there is provided a tire condition sensing system operable to be mounted to a wheel rim. The system may include a tire condition sensor capsule containing an electronic circuit for measuring a tire condition and for transmitting a signal indicative of the condition to a remote receiver. The system may further include a housing having a receptacle having a shape complementary to the capsule to receive the capsule snugly therein, a lock on the housing, cooperating with a cover of the capsule to lock the housing to the capsule, and a connector for connecting the housing to the wheel rim such that the capsule is between a portion of the wheel rim and the receptacle.

10
15 In accordance with yet another aspect of the invention there is provided a tire condition sensing system. The system may include a wheel rim, a tire condition sensor capsule containing an electronic circuit for measuring a tire condition and for transmitting a signal indicative of the condition to a remote receiver, a housing having a receptacle having a shape complementary to the capsule to receive the capsule snugly therein, a lock on the housing, cooperating with a cover of the capsule to lock the housing to the capsule, and a connector for connecting the housing to the wheel rim such that the capsule is between a portion of the wheel rim and the receptacle.

20
25 In accordance with another aspect of the invention there is provided a method of enabling measurement of a tire condition. The method may include installing on a vehicle a wheel to which is secured a housing having a receptacle in which a tire condition sensor capsule containing a tire condition sensor and signal transmitter is removably locked by a locking mechanism engaged with the capsule.

20
25
30

The present invention provides a versatile apparatus for mounting a tire condition sensor capsule to a wheel rim. As the capsule entirely encapsulates sensor and transmitter circuitry, the capsule may be treated as a separate, modular, replaceable unit. By using a housing to secure the tire condition sensor capsule to the wheel rim, expensive capsules can be replaced more easily without damage, enabling them to be removed, repaired and re-installed if desired. An inventory of various inexpensive housings may be made available to provide for mounting the same type of capsules in various ways, such as the ways described herein. An inventory of a plurality of different capsule shapes, sizes and configurations need not be maintained.

Other aspects and features of the present invention will become apparent to those ordinarily skilled in the art upon review of the following description of specific embodiments of the invention in conjunction with the accompanying figures.

BRIEF DESCRIPTION OF THE DRAWINGS

In drawings which illustrate embodiments of the invention,

- Figure 1 is a fragmented perspective view of a wheel rim to which an apparatus according to a first embodiment of the invention is connected;
- Figure 2 is a bottom perspective view of the apparatus shown in Figure 1;
- Figure 3 is a top perspective view of the apparatus shown in Figure 1;
- Figure 4 is a cross sectional view of the apparatus taken along lines 4-4 in Figure 3;
- Figure 5 is a fragmented perspective view of a wheel rim on which an apparatus according to a second embodiment of the invention is connected;
- Figure 6 is a bottom perspective view of the apparatus shown in Figure 5;
- Figure 7 is a top perspective view of the apparatus shown in Figure 5;

Figure 8 is a fragmented perspective view of a wheel rim on which an apparatus according to a third embodiment of the invention is connected;

Figure 9 is a top, perspective view of the apparatus shown in Figure 8;

5 Figure 10 is a fragmented section/perspective view of the wheel rim and apparatus shown in Figure 8; and

Figure 11 is a bottom, perspective view of the apparatus shown in Figure 8.

DETAILED DESCRIPTION

10 Referring to Figure 1, an apparatus for mounting a tire condition sensor capsule 10 to a wheel rim 12 is shown generally at 14. The apparatus 14 comprises a housing 16 having a receptacle complementary to the sensor capsule 10 to receive the sensor capsule therein. Referring to Figure 2, a lock, shown generally at 22 is provided on the housing 16 to cooperate with a cover 24 of the sensor capsule 10 to lock the housing to the sensor capsule. Referring to Figures 1 and 2 a connector 26 is also provided on the housing 16 for connecting the housing to the wheel rim 12 such that the sensor capsule 10 is between a portion of the wheel rim and the receptacle.

20 The tire condition sensor capsule 10 may be of the type that houses electronic circuits including a sensor circuit and transmitter circuit, for example, for measuring and transmitting a signal indicative of air pressure and/or temperature inside the space formed between the wheel rim 12 and a tire (not shown) fitted to the wheel rim. Such sensor capsules 10 can be made in mass quantities and may have a modular shape for interchangeability. The modular shape permits all electronics and sensors to be located within the sensor capsule so there are no extraneous protrusions or projections that may be susceptible to damage during tire installation, for example.

30 Referring to Figures 2 and 3, in this embodiment the housing 16 is formed by injection molding of plastic to form a relatively rigid structure having a relatively thin sheet-like wall 28 formed to have first and second spaced apart

opposite side portions **30** and **32** and first and second opposite spaced apart end portions **34** and **36** connected together by an intermediate portion **38**. These portions of the wall **28** define the receptacle in which the sensor capsule **10** is received as seen best in Figure 2. The sensor capsule **10** is thus received between the first and second spaced apart opposite side portions **30** and **32** and the first and second opposite spaced apart end portions **34** and **36** of the wall **28**.

In this embodiment, the first and second side portions **30** and **32** have generally the same width and thus extend away from the intermediate portion **38** by approximately the same distance. The first and second side portions **30** and **32** have first and second edge extremities **40** and **42** respectively which are terminated in first and second parallel contact surfaces **44** and **46** respectively, for contacting the wheel rim **12** when the housing **16** is installed as shown in Figure 1. In this embodiment, the first and second contact surfaces **44** and **46** are concaved to have a shape complementary to the portion of the wheel rim **12** on which the housing **16** and sensor capsule **10** will be installed. The housing **16** may be installed on a drop center of the wheel rim **12**, for example, away from tire mounting flanges so as not to interfere with tire mounting operations. Depending on the diameter of the wheel rim **12** on which the housing **16** will be installed, an arc of the first and second contact surfaces **44** and **46** may have a radius of between about 6 inches to about 36 inches, for example. For a 17 inch wheel rim, the contact surfaces may have a radius of about 7 inches, for example.

Referring to Figure 3, in this embodiment, the housing **16** is formed to have a relatively smooth contour with no protruding projections or sharp corners that may come into contact with the tire during installation. Also, for weight reduction, the housing **16** has a weight reducing void therein and in the embodiment shown the weight reducing void includes first and second spaced apart weight reducing voids **50** and **52** in the intermediate portion **38**. These weight reducing voids **50** and **52** are simply areas in the wall **28** that are open.

This reduces the weight of the housing 16, thus reducing its effect on the balance of the wheel rim 12.

Referring to Figure 4, the lock 22 on the housing is shown in greater detail. Desirably, the lock is on the wall 28 and more desirably on at least one of the first and second side portions 30 and 32 and more desirably, both. Referring to Figure 2, in this embodiment, the lock includes first, second, third and fourth clips 60, 62, 64 and 66. The first and third clips 60 and 64 are formed at the edge extremity 40 of the first side portion 30 and the second and fourth clips 62 and 66 are formed at the edge extremity 42 of the second side portion 32. Referring to Figures 2 and 4, the clips 60, 62, 64 and 66 are operable to cooperate and engage with a bottom edge and bottom planar surface of the sensor capsule 10 to lock the housing 16 to the sensor capsule.

In the embodiment shown in Figures 1-4, the connector 26 for connecting the housing 16 to the wheel rim 12, includes first and second mounting flanges 65 and 67 formed in the first and second end portions 34 and 36 of the housing respectively. This type of connector 26 is for use in conjunction with mounting seats 70 and 72 already installed or formed on the wheel rim 12. In this embodiment, the mounting seats 70 and 72 include first and second bent metal tabs 74 and 76 having portions that act as the mounting seats and wheel rim mounting portions, one of which is exemplified by item 78, which are mounted to the wheel rim 12. These wheel rim mounting portions (78) may be mounted to the wheel rim 12 by bonding, welding or rivets, for example. Generally, the bent metal tabs 74 and 76 are mounted in spaced apart relation along the drop center of the wheel rim 12 at a spacing suitable to permit alignment of the first and second mounting flanges 65 and 67 on the housing 16 with the mounting seats 70 and 72.

In this embodiment, the first and second mounting flanges 65 and 67 generally follow the contour of the contact surfaces 44 and 46 of the first and second side portions 32 and 34 and thus follow the contour of the drop center

of the wheel rim **12**. Each mounting flange **65** and **67** has reinforcing members, two of which are shown in Figure **1** at **80** and **82** and each mounting flange has a respective fastener receiver opening **84** and **86** seen best in Figure **2**, operable to receive a fastener as shown in Figure **1**, such as a rivet or screw to secure it to its corresponding mounting seat such that the sensor capsule **10** is held between a portion of the wheel rim **12** and the receptacle.

Referring to Figures **5** and **6** an apparatus according to a second embodiment of the invention is shown generally at **100**. The apparatus **100** is similar to the apparatus **14** according to the first embodiment with the exception that the first and second end portions **34** and **36** of the wall **28** cooperate to act as a strap holder operable to cooperate with a strap **102** that extends around the wheel rim to secure the housing **16** to the wheel rim. To do this, the first and second end portions **34** and **36** are formed with first and second openings **104** and **106** respectively, which in this embodiment are horizontally oriented slots for receiving the strap **102** therethrough. The strap **102** may be a large diameter hose-type clamp, for example.

In this embodiment, to define the openings **104** and **106**, the first and second end portions **34** and **36** have respective flat wall portions, only one of which is shown at **108** in Figure **7**, that extend at an angle inwardly of an outer surface **110** of the respective end portion (in this case the first end portion **34**). A lower wall portion **112** extends upwardly from an edge extremity **114** of the end portion, following the contour of the end portion **34** and terminates in a recessed edge **116** spaced apart from a facing edge **118** of the flat wall portion **108**. The recessed edge **116** allows for easy insertion of an end of the strap **102** into the slot formed between the recessed edge **116** and the facing edge **118**, during installation.

Referring to Figure **8** an apparatus according to a third embodiment of the invention is shown generally at **130**. This apparatus is similar to the

apparatus of the first and second embodiments with the exception that the connector for connecting the housing **16** to the wheel rim **12** includes a valve stem connector **132** operable to cooperate with a valve stem **134** of the wheel rim **12** to secure the housing to the wheel rim.

5

Referring to Figures **9** and **10**, the valve stem connector **132** includes a valve stem receptacle **136** in the first side portion **30** of the housing **16** for receiving a portion of the valve stem **134**. In particular, the valve stem receptacle is operable to receive a butt end **138** of the valve stem **134** used to admit and release air from a tire mounted to the wheel rim **12**. Referring to Figures **9**, **10** and **11** the valve stem connector further comprises an opening **140** in the housing **16**, in communication with the valve stem receptacle **136**, for receiving a fastener **142** operable to fasten the valve stem **134** in the valve stem receptacle **136**.

10

20050001

15

A top portion of the intermediate portion **38** of the wall **28** forming the housing **16** is shaped to form a recess **144** providing access to an opening coterminous with the opening **140** into which the fastener **142** may be inserted to extend through the opening **140** and into a threaded opening **148** in the butt end **138** of the valve stem **134**. The opening **140** and recess **144** thus enable the fastener **142** to be used to secure the butt end **138** of the valve stem **134** to the housing **16**. The valve stem **134** may then be secured to the wheel rim **12**, using conventional methods, as shown in Figure **10**, whereby the housing **16** and capsule **10** held thereby is secured to the wheel rim.

20

25

Referring to Figures **8**, **9** and **11** in this embodiment, the end portions **34** and **36** are shorter than the side portions **30** and **32**, to reduce weight and material usage since these portions are not used in connecting the housing **16** to the wheel rim **12** in this embodiment.

30

The lock for locking the housing **16** to the capsule **10** is the same as in the previously described embodiments.

In operation of the apparatus described herein, on being presented with a wheel rim **12** of a particular type, an installer may select from a plurality of housings **16** (such as the three housing configurations shown and described herein), a housing suitable for the particular type of wheel rim on which the capsule **10** is to be installed. Referring to Figure 3, on selecting an appropriate housing **16**, the installer may then insert the capsule **10** into the receptacle in the selected housing such that the clips **60**, **62**, **64** and **66** snap onto the under surface of the capsule, thereby locking the capsule in the receptacle to form a single unit comprised of the capsule and housing locked thereto. The capsule **10** is thus received and locked in the receptacle.

Then, the appropriate connecting arrangement for the housing **16** selected may be employed. Referring to Figure 1, to connect a housing **16** according to the first embodiment described herein to the wheel rim **12** the installer positions the housing **16** over the mounting seats **70** and **72** to align the openings in the flanges with the mounting seats and inserts a rivet, for example and then draws the rivet tight to secure the housing to the wheel rim such that the capsule **10** is positioned between the receptacle and the wheel rim. A tire may then be installed on the wheel rim **12** and then the wheel rim may be installed on a vehicle.

Referring to Figures 5 and 6, to connect a housing **16** according to the second embodiment described herein, after the capsule **10** is received and locked in the receptacle as described above, the installer inserts an end portion of a strap **102** through the opening **104** in the first end portion **34**, passes it under the capsule and then through the opening **106** in the second end portion **36** such that the strap is captured by the openings in the housing. The strap **102** is then wrapped around the circumference of the drop center of the wheel rim **12** and opposite ends of the strap are secured together using conventional methods. A tire may then be installed on the wheel rim **12** and then the wheel rim may be installed on a vehicle.

Referring to Figures 9 and 10, to connect a housing 16 according to the third embodiment described herein, after the capsule 10 is inserted and locked in the receptacle as described above the installer then inserts a fastener 142 into the recess 144 to extend through the opening 140 to protrude from the valve stem receptacle 136 and then screws the fastener into the butt end 138 of the valve stem 134 until the butt end is drawn into the valve stem receptacle. Then, the valve stem 134 is inserted through an opening in the wheel rim 12 and is secured thereto using conventional securing methods. The housing 16 is thus secured to the wheel rim 12 through the valve stem 134. A tire may then be installed on the wheel rim 12 and then the wheel rim may be installed on a vehicle.

The above described embodiments provide a versatile apparatus for mounting a tire condition sensor capsule to a wheel rim. As the tire condition sensor capsule entirely encapsulates the sensor and transmitter circuitry, the capsule may be treated as a separate, modular, replaceable unit. By using the housing described herein to secure the capsule to the wheel rim, i.e. not directly connecting the capsule to the wheel rim, expensive capsules can be replaced more easily without damage, enabling them to be removed, repaired and re-installed if desired. The housing may be damaged, even deliberately, to enable the capsule to be removed and a new inexpensive housing may be used to re-install the old capsule to the wheel rim. In effect, since the capsules are modular, any housing of the type described herein may be used. Thus an inventory of various inexpensive housings may be made available to provide for mounting the same type of capsules in various ways, such as the ways described herein. An inventory of a plurality of different capsule shapes, sizes and configurations need not be maintained.

While specific embodiments of the invention have been described and illustrated, such embodiments should be considered illustrative of the

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 10